400 SERIES

600 SERIES

700 SERIES

STANLEY®

FLOORING

WEAR RESISTANCE

Durable Supreme Guard UV Coating protects against daily scratches and keeps floors looking newer for longer.

WATERPROOF

100% waterproof core and surface resist spills and moisture for worry-free living.

ACOUSTIC SHIELD

Built-in sound absorption reduces footstep noise and creates a quieter, more comfortable home.

Five layers.
One reliable floor.



- **SUPREME GUARD UV COATING**
- **WEAR-RESISTANT LAYER**
- **DECORATIVE WOOD FILM**
- **SPC CORE** (STONE PLASTIC COMPOSITE)
- **HIGH-DENSITY IXPE UNDERLAY**

TOTAL BUILD UP **6,5 mm**

TECHNICAL SPECIFICATIONS

Wear Layer	**0,50 mm**
Total Thickness	**5 + 1,5 mm**
Plank Size	**228x1220 mm**
Installation	**i4F Drop-Lock Technology**
Water Resistance	**100% Waterproof**
Surface Treatment	**Supreme Guard UV Coating**
Acoustic Performance	**ΔLw = 20 dB**
Underfloor Heating	**Yes · max 27°C**
Use Class (EN)	**23 – 34**
Warranty	**Residential 25 yr** **Commercial 10 yr**

CERTIFICATIONS & STANDARDS

CE
EN 14041:2004/AC2006

ISO
9001:2015
14001:2015
45001:2018

Phthalate Free

EPD
INTERNATIONAL EPD SYSTEM

SCAN THE QR CODE FOR INSTALLATION & USER GUIDES

400 SERIES

Warm, rustic oaks with natural character — four inviting shades for cosy, lived-in homes.



HARVEST OAK

CT401



BARN OAK

CT402



RURAL OAK

CT403



YARD OAK

CT405



400 SERIES

HARVEST OAK

CT401

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





400 SERIES

BARN OAK

CT402

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





400 SERIES

RURAL OAK

CT403

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





400 SERIES

YARD OAK

CT405

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)



600 SERIES

Real oak character. Built to take on whatever commercial spaces throw at it.



WHEAT RUSTIC OAK

BB625



HONEY RUSTIC OAK

BB626



TOBACCO RUSTIC OAK

BB627



PURE NATURAL

BB628



DARK NATURAL

BB629



WARM NATURAL

BB630



SOFT NATURAL

BB631



DEEP NATURAL

BB632



600 SERIES

WHEAT RUSTIC OAK

BB625

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





600 SERIES

HONEY RUSTIC OAK

BB626

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





600 SERIES

TOBACCO RUSTIC OAK

BB627

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





600 SERIES

PURE NATURAL

BB628

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





600 SERIES

DARK NATURAL

BB629

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





600 SERIES

WARM NATURAL

BB630

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





600 SERIES

SOFT NATURAL

BB631

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





600 SERIES

DEEP NATURAL

BB632

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)



700 SERIES

Light, cool-toned oaks for calm, contemporary interiors — four refined shades, from the pale elegance of Opal Oak to the deep, sophisticated tone of Onyx Oak.



OPAL OAK

PS701



AZURE OAK

PS702



CRYSTAL OAK

PS703



ONYX OAK

PS704



700 SERIES

OPAL OAK

PS701

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





700 SERIES

AZURE OAK

PS702

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





700 SERIES

CRYSTAL OAK

PS703

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)





700 SERIES

ONYX OAK

PS704

TOTAL THICKNESS
5 + 1,5 mm

PLANK SIZE
228×1220 mm

WEAR LAYER
0,50 mm

SURFACE TEXTURE
Embossed in Register (EIR)



STANLEY®
FLOORING

PACKAGING & PALLET INFORMATION

PACKAGE

1,95 m²
7 pieces / box
20,36 kg

PALLET

87,62 m²
45 boxes
956 kg

STANLEY® and the STANLEY logo are registered trademarks of Stanley Black & Decker Inc.
All rights reserved.

Imported and distributed by Area Floors · Kiezel Kleine Brogel 57, 3990 Peer, Belgium
www.areafloors.com.tr ·
For customer services please contact: 2helpu.com